




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>A61M 29/02, 25/01</b>	<b>A1</b>	(11) International Publication Number: <b>WO 95/02430</b> (43) International Publication Date: 26 January 1995 (26.01.95)
<p>(21) International Application Number: PCT/US94/07960</p> <p>(22) International Filing Date: 15 July 1994 (15.07.94)</p> <p>(30) Priority Data: 08/092,550 15 July 1993 (15.07.93) US</p> <p>(71) Applicant: ADVANCED CARDIOVASCULAR SYSTEMS, INC. [US/US]; 3200 Lakeside Drive, Santa Clara, CA 95052 (US).</p> <p>(72) Inventors: GHARIBADEH, Ramsin; 305 Otono Court, San Jose, CA 95111 (US). FELTOVICH, Susan, M.; 3480 Granada Avenue #301, Santa Clara, CA 95051 (US). HILARIO, Estela, H.; 887 Altos Oaks Drive, Los Altos, CA 94024 (US). THORNTON, Troy, L.; 258 Commons Lane, Foster City, CA 94404 (US).</p> <p>(74) Agents: LYNCH, Edward, J.; Crosby, Heafey, Roach &amp; May, 1999 Harrison Street, Oakland, CA 94612 (US) et al.</p>	<p>(81) Designated States: CA, JP, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p><b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>	

(54) Title: RAPID EXCHANGE TYPE INTRALUMINAL CATHETER WITH GUIDING ELEMENT



## (57) Abstract

An intraluminal catheter, particularly a dilatation catheter for PTCA procedures, which is adapted for rapid exchange during an intraluminal procedure and which also allows for the exchange of the guidewire without loss of access to the intraluminal region about the distal end of the catheter. The catheter has a guidewire lumen which extends essentially the length of the catheter. A wall of the catheter shaft which defines at least part of the guidewire lumen has a first slit from the proximal end of the catheter to an area proximal to the second guidewire port and a second slit which extends from the proximal guidewire port to a location spaced proximally from the distal end of the catheter. Also disclosed is an adapter having a slit which is continuous with the slit in the proximal extremity of the catheter shaft which facilitates separation of the guidewire and the catheter when the adapter is fixed to the proximal end of the catheter shaft. A guidewire directing element disposed in the guidewire lumen which has a flexible arm which crosses the guidewire lumen so as to guide a guidewire out the second guidewire port when the guidewire is advanced proximally through the guidewire lumen and which is flexible enough to be pushed aside when a replacement guidewire is advanced distally through the guidewire lumen.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

**RAPID EXCHANGE TYPE INTRALUMINAL CATHETER**  
**WITH GUIDING ELEMENT**

**BACKGROUND OF THE INVENTION**

This invention generally relates to a rapid exchange type intraluminal catheter system which is suitable for intravascular procedures such as percutaneous transluminal coronary angioplasty (PTCA) and which allows for the exchange of the catheter or the guidewire during such procedures without loss of access to the patient's distal arterial location.

In PTCA procedures, a guiding catheter having a preshaped distal tip is percutaneously introduced into the cardiovascular system of a patient and advanced therein until the preshaped distal tip thereof is disposed within the aorta adjacent to the ostium of the desired coronary artery. The guiding catheter is twisted or torqued from the proximal end to turn the distal tip of the guiding catheter so that it can be guided into the coronary ostium. A dilatation catheter having a balloon on its distal end

and a guidewire slidably disposed within an inner lumen of the dilatation catheter are introduced into and advanced through the guiding catheter to its distal tip. The distal tip of the guidewire is usually manually shaped (*i.e.* curved) before the guidewire is introduced into the guiding catheter along with the dilatation catheter. The guidewire is first advanced out the distal tip of the guiding catheter, into the patient's coronary artery, and torque is applied to the proximal end of the guidewire, which extends out of the patient, to guide the curved or otherwise shaped distal end of the guidewire as the guidewire is advanced within the coronary anatomy until the shaped distal end of the guidewire enters the desired artery. The advancement of the guidewire within the selected artery continues until its distal end crosses the lesion to be dilated. The dilatation catheter is then advanced out of the distal tip of the guiding catheter, over the previously advanced guidewire, until the balloon on the distal extremity of the dilatation catheter is properly positioned across the lesion. Once properly positioned, the dilatation balloon is inflated to a predetermined size with radiopaque liquid at relatively high pressures (*e.g.*, 4-12 atmospheres) to dilate the stenosed region of the diseased artery. The balloon is then deflated so that the dilatation catheter can be removed from the dilated stenosis and blood flow can resume through the dilated artery.

A rapid exchange type dilatation catheter has a short guidewire-receiving sleeve or inner lumen extending a short distance

through just the distal portion of the catheter shaft. The sleeve or inner lumen preferably extends proximally at least about 10 cm, typically about 30 cm, from a first guidewire port in the distal end of the catheter to a second guidewire port. A slit may be provided in the catheter wall defining the short guidewire receiving lumen which extends distally from the second guidewire port to a location proximal to the inflatable balloon to facilitate the separation of the catheter from the guidewire. The catheter is advanced within the patient's vascular system with the guidewire disposed within the guidewire receiving inner lumen in the distal section of the catheter shaft in a conventional fashion as previously described. Alternatively, the guidewire may be first advanced within the patient's vasculature until the distal end of the guidewire extends distally to the stenosis to be dilated and then the catheter is mounted onto the proximal end of the in-place guidewire and then advanced over the guidewire until the dilatation balloon is properly disposed across the stenosis. The structure of the catheter allows for the rapid exchange of the catheter without the need for an exchange wire or adding a guidewire extension to the proximal end of the guidewire.

Rapid exchange type catheters are available from the licensee of the present invention, Advanced Cardiovascular Systems, Inc., under the trademark ACS RX® which are basically described and claimed in U.S. Patent 5,061,273 (Yock) and U.S. Patent 4,748,982 (Horzewski *et al.*).

The catheter design embodying the Yock and Horzewski *et al.* improvements has been widely praised by members of the medical profession and it has met with much commercial success in the market place. However, there are some inconveniences in its use because the catheter does not allow for the exchange or replacement of the guidewire. For example, the shaped distal tip of the guidewire may become deformed in use or the shape of the distal tip or the size of the guidewire may be found to be no longer suitable for the particular procedure within the patient's vasculature. In this instance the physician might want to remove the guidewire and reshape the distal tip or replace the first guidewire with another having the desired size, stiffness or shape. However, when the guidewire in a dilatation catheter system embodying the Yock and Horzewski *et al.* improvements is removed, access to the desired distal arterial location through the distal guidewire lumen of the catheter is lost. Unfortunately, there is no way to clinically determine before the guidewire is inserted into the patient in an angioplasty procedure whether a guidewire or a catheter will have to be exchanged during the procedure.

What has been needed and heretofore unavailable is an easily usable intravascular catheter system which allows for the rapid exchange of either the catheter or the guidewire during an intravascular procedure without losing access to the desired distal region of the patient's arterial system. The present invention satisfies this and other needs.

### SUMMARY OF THE INVENTION

This invention is directed to a rapid exchange type intraluminal catheter system which allows for the exchange of a guidewire and which can also be used as an over-the-wire type intraluminal catheter without losing access to the location of the distal portion of the catheter within the patient's body lumen.

The catheter system of the invention generally comprises an elongated catheter shaft having proximal and distal ends, a guidewire lumen extending from the proximal end of the catheter shaft to the distal end of the catheter shaft, a first guidewire port in the distal end of the catheter shaft and a second guidewire port spaced a short distance, *e.g.* from about 10 cm to usually not more than about 50 cm, from the distal end of the catheter shaft, both of said guidewire ports being in communication with the guidewire lumen. A guidewire guiding means is provided within the guidewire lumen to direct the proximal end of a first guidewire being proximally advanced through the guidewire lumen out the second guidewire port, but which allows a second guidewire to be advanced through the guidewire lumen from a location proximal to the guiding means and precludes excursions of the second guidewire out the second guidewire port. A presently preferred guidewire guiding means generally has a support base, preferably tubular, which is adapted to be secured within the

guidewire lumen proximal to the second guidewire port and a flexible arm extending distally within the guidewire lumen from the same side of the guidewire lumen in which the second guidewire port is located to the side opposite thereto so as to guide the proximal end of the proximally

5 advancing first guidewire out the second guidewire port. The arm of the guiding means has sufficient flexibility to be pushed aside out of the way when a second guidewire is being advanced distally through the guidewire lumen from a location proximal to the base of the guidewire guiding means.

The flexible arm of the guidewire guiding element, when the  
10 guiding element is properly disposed within the guidewire lumen, extends distally from the base of the guiding element and crosses the guidewire lumen inwardly so that a guidewire being advanced proximally through the guidewire lumen will be directed out of the guidewire lumen through the second guidewire port spaced proximally from the distal end of the catheter  
15 shaft. The guidewire guiding element, particularly the flexible arm thereof, is preferably formed of a superelastic NiTi alloy which has been thermomechanically treated to provide a relatively large range of strain at relatively high tensile properties. A suitable alloy material consists essentially of about 30 to about 52% titanium and the balance nickel and up  
20 to about 10% of one or more additional alloying elements; such additional alloying elements may be selected from the group consisting of iron, cobalt, chromium, platinum, and palladium in amounts up to 3% each and copper



and vanadium in amounts of up to 10% each. As used herein all percentages with respect to composition are atomic percent unless noted otherwise. The guiding element is machined from a tubular product which has been formed by cold working at least 10% and heat treating after the cold working at a temperature from about 300° to about 600° C. If needed the tubular product may be straightened before or during the heat treatment. The machined tubular product has a finished martensite-to-austenite transformation temperature of about -25° to about 45° C.

An inflatable member such as a dilatation balloon may be provided on the distal section of the catheter shaft which has an interior in fluid communication with an inflation lumen which extends from the proximal end of the catheter shaft.

To facilitate a catheter exchange during an intravascular procedure, a slit should be provided in a wall of the proximal section of the catheter shaft which defines at least in part the guidewire receiving lumen extending therein. In this manner the catheter shaft can be readily separated from the guidewire disposed within the guidewire lumen. The slit extends from the proximal end of the catheter shaft to a location proximal to the base of the guidewire guiding member disposed within the guidewire lumen. Another slit may be provided in the distal portion of the catheter shaft which extends distally from the second guidewire port to a location spaced proximally from the distal end of the catheter which facilitates

separation from a guidewire which is disposed within the guidewire lumen in the distal portion of the catheter and extends out the second guidewire port.

5 An adapter is provided on the proximal end of the catheter shaft which has an inner lumen for directing a guidewire into the guidewire lumen in the proximal section of the catheter shaft. The adapter is preferably a multi-arm adapter with one arm for directing inflation fluid into the inflation lumen and a second arm which has an inner lumen adapted to direct a guidewire into the guidewire receiving lumen of the catheter shaft. In one presently preferred embodiment, the arm of the adapter which directs a guidewire to the guidewire lumen in the catheter shaft has a slit continuous with the slit in the proximal section of the shaft to facilitate the complete separation of the catheter shaft from a guidewire.

15 One of the advantageous features of the catheter of the invention is that it can be initially advanced within a patient's vascular system or other body lumen either in a rapid exchange mode with the guidewire extending through just the distal portion of the catheter shaft in the guidewire receiving lumen therein or in a conventional over-the-wire mode with the guidewire extending through the guidewire receiving lumen throughout essentially the entire length of the catheter shaft. The catheter design allows for the exchange of the catheter while the guidewire remains

20

in place or the replacement of the guidewire while the catheter remains in place during an intraluminal procedure such as a PTCA.

To exchange an in-place guidewire during an intraluminal procedure with the catheter system of the invention, the in-place catheter is manually held so as to maintain its position within the patient's vasculature to ensure access to the position therein. The in-place guidewire may then be removed from the guidewire-receiving inner lumen of the catheter and the patient by merely pulling on its proximal end which extends out of the patient. While the in-place guidewire is being removed from the inner lumen of the in-place catheter, the distal end of the in-place catheter is maintained at the desired location within the patient's artery. A replacement guidewire is inserted into the second arm of the adapter and advanced through the guidewire receiving lumen in the proximal and distal sections of the catheter shaft and out the guidewire port in the distal end of the catheter shaft to the desired location within the patient's body lumen. As the replacement guidewire advances through or by the guidewire guiding member, it pushes the flexible arm thereof out of the way, thereby preventing an excursion of the replacement guidewire out the second guidewire lumen. It may be desirable in some instances to have the replacement guidewire already inserted at least into the proximal portion of the guidewire-receiving inner lumen, but proximal to the guidewire guiding means, before the in-place guidewire is removed from the distal portion of

the inner lumen so that there is little chance of losing access to the location in the body lumen by the accidental movement of the in-place catheter.

When the replacement guidewire is advanced through the in-place catheter and properly positioned in a desired location therein, *e.g.* across a stenosis  
5 in a patient's artery which is to be dilated, the catheter may then be advanced over the replacement guidewire to the desired location so as to perform the desired diagnostic or therapeutic treatment therein.

The intravascular catheter of the invention also allows for the removal and reinsertion of the same guidewire, for example, when the  
10 physician wishes to change the shape of the distal end of a guidewire during a procedure. In this operative modality, the in-place guidewire can be withdrawn in essentially the manner described above, the distal tip thereof reshaped and then reintroduced into the in-place catheter, in essentially the same manner as described above, by advancing the guidewire through the  
15 adapter on the proximal end of the catheter shaft into the guidewire receiving lumen extending therein and out the first guidewire port in the distal end of the catheter into the patient's coronary anatomy.

To replace the catheter of the invention during a PTCA procedure, the in-place guidewire is manually held so as to maintain its  
20 position within the patient's vasculature to ensure access to the position therein, while the in-place dilatation catheter is pulled proximally over the guidewire by the proximal end of the catheter. If the catheter is being used

in the rapid exchange mode, the catheter is withdrawn from the patient by peeling the dilatation catheter off of the guidewire through the slit extending distally from the second guidewire port until the distal end of the dilatation catheter exits the proximal end of the guiding catheter, or an  
5 adapter attached thereto, at which point the portion of the guidewire exposed distal to the dilatation catheter can be manually held in position while the catheter is removed from the proximal end of the guidewire. If the catheter has been used in an over-the-wire mode, the in-place guidewire exits the second arm of the adapter on the proximal end of the catheter  
10 shaft. The catheter is withdrawn from the patient by peeling the dilatation catheter off the guidewire through the slits provided in the adapter and proximal section of the shaft to a location in the shaft proximal to the base of the disposed guidewire guiding element. The remaining distal section (about 10 cm to usually not more than about 50 cm) of the catheter can be  
15 removed from the proximal end of the guidewire while manually holding the exposed portion of the guidewire in position.

Once the catheter has been separated from the proximal end of the in-place guidewire, the proximal end of the in-place guidewire is inserted into the guidewire port in the distal end of a replacement catheter  
20 having the construction of the present invention. The distal portion of the replacement catheter shaft is advanced distally over the in-place guidewire in the guidewire lumen until the proximal end of the guidewire encounters

the flexible arm of the guidewire guiding element which guides the proximal end out the second guidewire port. At this point, the portion of the guidewire which extends out the second guidewire port may be manually held while the replacement catheter in a rapid exchange mode is further advanced into the patient's vasculature over the in-place guidewire to perform the desired intravascular procedure.

As will become more apparent from the following detailed description of the invention, the intraluminal catheter system of the invention allows for a wide variety of intravascular procedures which were heretofore difficult, if not impossible, to perform with a single catheter system. These and other advantages of the invention will become more apparent from the following detailed description of the invention when taken in conjunction with the accompanying exemplary drawings.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is an elevational view, partially in section, of a dilatation catheter which embodies features of the invention.

Fig. 2 is a plan view of the proximal end of the catheter shown in Fig. 1 taken along the lines 2-2.

Fig. 3 is a transverse, cross-sectional view of the catheter shown in Fig. 1 taken along the lines 3-3.

Fig. 4 is a transverse, cross-sectional view of the catheter shown in Fig. 1 taken along the lines 4-4.

Fig. 5 is a transverse, cross-sectional view of the catheter shown in Fig. 1 taken along the lines 5-5.

5 Fig. 6 is a longitudinal cross-sectional view of a distal portion of the catheter shown in Fig. 1 with a guidewire extending through a guidewire lumen from the proximal end of the catheter shaft and out the guidewire port in the distal end of the catheter.

10 Fig. 7 is a perspective view of the guidewire guiding element shown in Figs. 1 and 6.

#### **DETAILED DESCRIPTION OF THE INVENTION**

Figs. 1-6 illustrate a rapid exchange type dilatation catheter 10 embodying features of the invention which allows for the exchange of a guidewire while the catheter remains in place within a patient's arterial system so as to avoid loss of the arterial position and also allows for the exchange of the catheter while a guidewire remains in place. The catheter 10 generally comprises an elongated catheter shaft 11, an inflation lumen 12 adapted to direct inflation fluid from the proximal end of the catheter shaft to the interior of an inflatable dilatation balloon 13 on a distal portion of the catheter shaft and a guidewire-receiving inner lumen 14 extending therein from the proximal end of the catheter shaft to a first guidewire port

15

20

15 in the distal end of the catheter shaft. A second guidewire port 16,  
which is also in communication with the guidewire lumen 14, is provided in  
the wall forming at least in part the catheter shaft 11 at a location a short  
distance, *e.g.* 10 to 50 cm from the distal end of the catheter shaft and a  
5 substantial distance from the proximal end of the catheter shaft.

As shown in Figs. 3-5 the proximal section 17 and the distal  
section 18 of the catheter shaft 11 are of a dual lumen construction with the  
inflation lumen 12 and guidewire receiving lumen 14 having circular  
transverse cross-sections. The inflation lumen 12 terminates at the  
10 proximal end of the balloon 13 and is in fluid communication with the  
interior of the balloon. Tubular extension 20 of the catheter shaft 11, which  
defines in part the guidewire receiving lumen 14, extends to the distal end  
thereof. The distal end of the balloon 13 is sealingly secured to the distal  
end of the extension 20 by suitable means such as heat bonding or an  
15 adhesive. The inflation lumen 12 within the proximal section 17 is  
preferably provided with supporting inner tubular member 21 formed of  
high strength material such as a polyimide, stainless steel or a suitable  
superelastic NiTi alloy. The distal part 23 of the supporting inner tubular  
member 21 may be formed of tubular stock with a thinner wall as shown in  
20 Figs. 1 and 6. The proximal waist 22 of the balloon 13 is secured in a  
suitable manner, *e.g.* heat bonding or an adhesive, to the exterior of the  
distal section 18 of the shaft 11.



The proximal section 17 of the catheter shaft 11 is provided with a proximal slit 24 which extends from the proximal end of the shaft 11 to a location proximal to the guidewire guiding member 25. The distal catheter shaft section 18 is also provided with distal slit 26 which extends  
5 from the second or proximal guidewire port 16 to a location 27 proximal to the proximal waist 22 of the balloon 13.

Guidewire 28, which is slidably disposed within inner guidewire lumen 14, has a coil 29 on its distal end which is shown in Fig. 1 extending out the first guidewire port 15 and an elongated core member 30  
10 which is shown extending through the guidewire lumen 14 and out the second guidewire port 16 as would be utilized in a rapid exchange mode. A replacement guidewire 31 is shown within guidewire lumen 14 in the proximal portion of the catheter shaft 11.

A multi-arm adapter 32, which is provided on the proximal end  
15 of the catheter shaft 11, has one arm 33 with an inner lumen 34 which is adapted to introduce inflation fluid into the inflation lumen 12 and a second arm 35 with an inner lumen 36 which is adapted to receive a replacement guidewire 31 and guide it into the guidewire receiving lumen 14 within the catheter shaft 11. The proximal end of the catheter shaft 11 is provided  
20 with an insert 37 which fits into the interior of the adapter 32 as shown. The second arm 35 of adapter 32 is provided with a slit 38 and the insert 37 is provided with a slit 39, both of the slits being continuous with the slit 24

in the proximal section 17 of the catheter shaft 11. A portion of the insert 37 sealingly connects the inner lumen 34 with the inner inflation lumen 12 within the catheter shaft 11. The insert 37 may be formed as a separate element and then secured to the proximal end of the catheter shaft 11 or  
5 formed as part of the catheter shaft as depicted in Fig. 1.

A radiopaque marker 40 is disposed about the tubular extension 20 which extends within the interior of the balloon 13 to facilitate the fluoroscopic observation thereof during an intravascular procedure. A visual marker (not shown) may also be provided on the proximal section 17  
10 of the catheter body 11 to allow the physician to fluoroscopically determine the location of the proximal guidewire port 16 during an intravascular procedure. Other visual markers (not shown) for the brachial and femoral arteries may be provided on the proximal section 17 of the shaft 11 in a conventional fashion.

15 Fig. 6 depicts the guidewire guiding element 25 with the flexible arm 41 being displaced laterally by the replacement guidewire 31 as it is advanced distally through the guidewire lumen 14.

Fig. 7 illustrates in perspective a guidewire guiding element 25 shown in Fig. 1 which has a tubular base 42 adapted to be tightly fitted or  
20 otherwise secured within the guidewire lumen 14 as shown in Fig. 1, and flexible arm 41. The arm 41 is formed so as to extend across the guidewire lumen from a location adjacent to the second guidewire port 16, as shown in

Fig. 1, and guide the proximal end of a guidewire 28 which is being advanced proximally through the inner lumen 14 out the second or proximal guidewire port 16. At least the flexible arm 41, preferably the entire element 25, is formed of a superelastic alloy having a final austenite transformation temperature ( $A_f$ ) of less than about 40° C. The preferred alloy is a nickel-titanium containing alloy which preferably contains about 32 to about 52% titanium and the balance nickel and up to 10% additional alloying elements. The additional alloying elements may include iron, cobalt, chromium, platinum and palladium in amounts up to about 3% and cooper and vanadium in amounts up to 10% each. A nickel content exceeding 50% causes brittleness and prevents effective cold marking. The element is formed, *e.g.* machined, from superelastic tubing having the desired composition and having been processed by cold working from about 10 to about 75% and thermally treating from about 300° to about 600° C. If necessary, the tubular product may be straightened during or prior to the thermal treatment.

The catheter system of the invention can be inserted into the patient in a conventional rapid exchange fashion with the guidewire 28 preloaded within the inner lumen 14 in the distal section 18 and extending proximally out of the proximal guidewire port 16 or it can be inserted in a conventional over-the-wire fashion with the guidewire extending through the entire length of the guidewire lumen 14 and out the second arm 35 of

the adapter 32. When it becomes desirable or necessary at any time during the intravascular procedure to remove or replace either the catheter 10 or the guidewire 28 either may be removed by pulling on the proximal end thereof which extends out of the patient while the catheter or guidewire which remains within the patient is held in position in order to maintain access to the desired intravascular location about the distal end of the catheter or guidewire which remains.

If the guidewire 28 is to be removed when in a rapid exchange mode of operation, the catheter 10 is held in place while the guidewire is pulled out of the proximal end of the guiding catheter (not shown) and adapter thereon. In the over-the-wire mode the guidewire will extend out of the proximal end of the arm 35 of the adapter 32. After the guidewire 28 has been removed from the catheter 10, a replacement guidewire 31 may then be inserted through the end of the arm 35 of the adapter 32 into the inner lumen 14 and advanced therein until the guidewire exits the distal guidewire port 15 in the distal end of the catheter body 11 into the patient's coronary artery. Once the replacement guidewire 31 is properly positioned within the patient's artery, *e.g.* across a stenosis to be dilated, the dilatation catheter 10 may then be further advanced within the artery, if necessary, over the replacement guidewire to the desired location therein to perform the dilatation or other diagnostic or therapeutic procedure.

If the catheter 10 is to be removed and the guidewire 28 exits the proximal port 16 of the catheter, *i.e.* the catheter is used in the rapid exchange mode, the catheter is withdrawn and separated from the guidewire through the distal slit 26 until a section of the guidewire 28 is exposed distal to the catheter. When the distal end of the catheter 10 is pulled out of the proximal end of the guiding catheter (or the adapter thereon), the exposed portion of the guidewire 28 distal to the distal end of the catheter 10 may be manually gripped to hold it in place and the catheter 10 can then be removed from the proximal end of the guidewire. If the catheter 10 is being used in an over-the-wire mode with the proximal end of the guidewire extending out of the proximal end of the guiding catheter, the guidewire and the catheter are separated while the catheter is being withdrawn from the proximal end of the guiding catheter (or adapter thereon) by separating the catheter from the guidewire or pulling the catheter off the guidewire via the adapter slit 38, the adapter insert slit 39 and the slit 24 in the wall of the proximal section 17 of the shaft 11. The rest of the procedure is essentially the same as that previously described.

When the catheter 10 has been removed, a replacement catheter may be mounted onto the proximal end of the guidewire 30 by inserting the proximal end of the guidewire through distal guidewire port 15 in the distal end of the replacement rapid exchange type catheter and advancing the catheter over the guidewire disposed within a guidewire

receiving lumen 14 of the replacement catheter. The guiding means 25 guides the proximal end of the guidewire out the proximal guidewire port 16 in a rapid exchange fashion. The proximal end of the guidewire 30 is held while the replacement catheter is advanced within the patient in a conventional manner as described in Yock or Horzewski *et al.* which have been incorporated herein.

The catheter body 11 can be formed by conventional techniques, *e.g.* extruding, from materials already found useful in intravascular catheters such as polyethylene, polyvinyl chloride, polyesters and composite materials. The various components of the catheter can be joined by suitable adhesive such as the acrylonitrile based adhesive sold as Loctite™ 405. Heat shrinking or heat bonding may also be employed where appropriate. A venting means may be provided to remove air from the interior of the balloon before the catheter is inserted into the patient such as described in U.S. Patent 4,638,805 (Powell) and U.S. Patent 4,821,722 (Samson *et al.*) which have been incorporated herein.

The size of the catheter body 11 and the guidewire-receiving inner lumen 14 thereof to a large extent are determined by the size of the guidewires 28 and 31 to be employed and the size of the artery or other body lumen through which the catheter must pass. Generally, the diameter of the inner lumen 14 is sufficient to accommodate the guidewire and to allow it to be slidably disposed therein. The diameters of guidewires for

coronary use can vary from about 0.006 to about 0.035 inch (0.2-0.89 mm) in diameter, and the inner diameter of the guidewire-receiving inner lumen 14 of the catheter 10 should be about 0.001 to about 0.005 inch (0.025-0.127 mm) larger than the diameter of the guidewire. The catheter body 11 is  
5 sufficiently long to extend from outside the proximal end of a guiding catheter, which likewise extends out of the patient, to a stenosis to be treated within the patient's vascular system (or other desired location therein), *e.g.* from about 100 to about 150 cm when a Seldinger approach  
10 through the femoral artery is employed to introduce the catheter 10 into the patient's vasculature. The wall forming the catheter must be of sufficient thickness and strength so that it can be pushed over the guidewires 28 and 31 to the desired location within the patient's blood vessel.

While the invention has been described herein in terms of certain presently preferred embodiments directed to balloon dilatation  
15 catheters for use in coronary angioplasty procedures, those skilled in the art will recognize that the catheter of the invention may be used in a variety of body lumens. For example, the invention can be utilized in various diagnostic and therapeutic intraluminal catheters. Additionally, the catheter body may be of concentric construction rather than the dual lumen  
20 construction shown herein. Other modifications and improvements may be made to the invention without departing from the scope thereof.

WHAT IS CLAIMED IS:

1           1.     An intraluminal catheter suitable for performing an  
2     intraluminal procedure within a patient's body lumen which permits the  
3     exchange of a guidewire during the procedure without loss of access to the  
4     location of the distal portion of the catheter within the patient's body  
5     lumen, comprising:

6               a)     an elongated catheter shaft having proximal and distal  
7     ends, a guidewire lumen extending through the catheter shaft to the  
8     distal end thereof, a first guidewire port in the distal end of the  
9     catheter shaft in fluid communication with the guidewire lumen and  
10    a second guidewire port in a distal portion of the catheter shaft which  
11    is spaced a short distance from the distal end of the catheter shaft  
12    and a substantial distance from the proximal end of the catheter  
13    shaft and which is in fluid communication with the guidewire lumen  
14    in the distal portion of the catheter shaft; and

15              b)     a guidewire directing means disposed within the  
16    guidewire lumen having means which direct a guidewire advancing  
17    proximally through the guidewire lumen out the second guidewire  
18    port and which prevent a guidewire advancing distally through the  
19    guidewire lumen from passing through the second guidewire port.



1           2.     The catheter of claim 1 wherein the guidewire directing means  
2 includes a base which is located within the guidewire lumen and a flexible  
3 arm which is secured by one end thereof to the base, which extends distally  
4 from the base and which crosses the guidewire lumen from a side having  
5 therein the second guidewire port to a side opposite thereto so as to form a  
6 guideway adapted to urge out the second guidewire port a guidewire which  
7 is advanced proximally through the guidewire lumen from the distal end of  
8 the catheter shaft.

1           3.     The catheter of claim 2 wherein at least the flexible arm of the  
2 guidewire directing means is formed of a superelastic alloy containing  
3 nickel and titanium.

1           4.     The catheter of claim 3 wherein the alloy containing nickel and  
2 titanium has an A<sub>c</sub> temperature less than 40 °C.

1           5.     The catheter of claim 4 wherein the alloy contains 32-52%  
2 titanium and the balance nickel and up to about 10% other alloying  
3 elements.

1           6.     The catheter of claim 1 wherein a wall of the catheter shaft  
2 defining at least in part the guidewire lumen is provided with a slit

3 extending longitudinally from the proximal end of the catheter shaft to a  
4 location proximal to the guidewire directing means and transversely  
5 through the wall to be in communication with the guidewire lumen.

1 7. The catheter of claim 1 wherein a wall of the catheter shaft  
2 defining at least in part the guidewire inner lumen is provided with a slit  
3 extending longitudinally from the proximal guidewire port to a location  
4 spaced proximally from the distal end of the catheter and transversely  
5 through the wall to be in communication with the guidewire lumen.

1 8. The catheter of claim 1 wherein an adapter is provided on the  
2 proximal end of the catheter shaft which has an arm with an inner lumen  
3 which is adapted to receive a guidewire therein and which is in  
4 communication with the guidewire lumen of the catheter body.

1 9. The catheter of claim 8 wherein the arm of the adapter has a  
2 slit continuous with the slit in the proximal section of the catheter shaft to  
3 facilitate the separation therefrom of a guidewire disposed within the inner  
4 lumen of the arm.

1           10.    The catheter of claim 1 wherein the second guidewire port is  
2 spaced at least about 10 cm from the distal end of the catheter shaft and a  
3 substantial distance from the proximal end of the catheter shaft.

1           11.    A readily exchangeable dilatation catheter suitable for  
2 performing an angioplasty procedure within a patient's artery which  
3 permits the exchange of a guidewire during an angioplasty procedure  
4 without loss of access to the location of the distal portion of the catheter  
5 within the patient's artery, comprising:

6                   a)    an elongated catheter shaft having proximal and distal  
7 ends, an inflation lumen extending from the proximal end of the  
8 catheter shaft to a location in a distal section of the catheter shaft, a  
9 guidewire lumen extending from the proximal end of the catheter  
10 shaft to a first guidewire port in the distal end of the catheter shaft  
11 and a second guidewire port spaced a short distance from the distal  
12 end of the catheter shaft which is in fluid communication with the  
13 guidewire lumen;

14                   b)    an inflatable member on the distal section of the  
15 catheter shaft which has a interior in fluid communication with the  
16 inflation lumen;

17                   c)     an adapter on the proximal end of the catheter shaft  
18                   having a first arm with an inner lumen which is adapted to direct  
19                   inflation fluid into the inflation lumen;

20                   d)     a guidewire directing means disposed within the  
21                   guidewire lumen which directs a guidewire advancing proximally  
22                   through the guidewire lumen out the second guidewire port and  
23                   which prevents a guidewire advancing distally through the guidewire  
24                   lumen from a location proximal to the second guidewire port from  
25                   passing through the second guidewire port.

1                   12.    The dilatation catheter of claim 11 wherein a wall forming at  
2                   least part of the catheter shaft is provided with a slit extending from the  
3                   proximal end of the catheter shaft to a location proximal to the guidewire  
4                   directing means.

1                   13.    The dilatation catheter of claim 11 wherein a wall forming at  
2                   least part of the catheter shaft is provided with a slit extending from the  
3                   second guidewire port to a location proximal to the inflatable member.

1                   14.    The dilatation catheter of claim 11 wherein the adapter on the  
2                   proximal end of the catheter shaft has a second arm with an inner lumen

3 which is adapted to receive a guidewire therein and which is in  
4 communication with the guidewire receiving lumen.

1 15. The dilatation catheter of claim 14 wherein the second arm of  
2 the adapter has a slit continuous with the slit in the proximal section of the  
3 shaft to facilitate the separation therefrom of a guidewire disposed within  
4 the inner lumen of the second arm.

1 16. The dilatation catheter of claim 11 wherein the second  
2 guidewire port is spaced proximal to the inflatable member.

1 17. The dilatation catheter of claim 11 wherein the second  
2 guidewire port is spaced at least about 10 cm from the distal end of the  
3 catheter shaft and a substantial distance from the proximal end of the  
4 catheter shaft.

1 18. The dilatation catheter of claim 11 wherein the inflatable  
2 member has an elongated waist.

1 19. A guidewire directing means comprising a tabular base  
2 adapted to be secured within a guidewire lumen of an elongated catheter  
3 and a flexible arm extending from the base which is shaped to cross the

- 4 guidewire lumen of the elongated catheter so as to direct a guidewire out a
- 5 guidewire port provided in the catheter.





FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7





## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 94/07960

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 A61M29/02 A61M25/01

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US,A,4 552 554 (GOULD ET AL.) 12 November 1985 see abstract; claim 1; figures 1-4 ---	19
A	EP,A,0 388 112 (SCHNEIDER (USA) INC.) 19 September 1990 see column 2, line 40 - column 3, line 44; claims 1,2; figures 1-2E ---	1,2,6-13
A	EP,A,0 282 143 (C.R.BARD, INC.) 14 September 1988 see column 2, line 36 - column 3, line 57; claims 1,8-11; figures 1-4,10 ---	1,2,6-9, 11-13,19
A	US,A,5 161 534 (BERTHIAUME) 10 November 1992 see abstract; figures 1-4 --- -/--	11-14



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents :

- \* "A" document defining the general state of the art which is not considered to be of particular relevance
- \* "E" earlier document but published on or after the international filing date
- \* "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \* "O" document referring to an oral disclosure, use, exhibition or other means
- \* "P" document published prior to the international filing date but later than the priority date claimed

\* "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\* "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\* "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\* "&" document member of the same patent family

Date of the actual completion of the international search

25 November 1994

Date of mailing of the international search report

06.12.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Michels, N

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US 94/07960

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 518 205 (ADVANCED CARDIOVASCULAR SYSTEMS, INC.) 16 December 1992 ----	
A	WO,A,92 17236 (BOSTON SCIENTIFIC CORPORATION) 15 October 1992 ----	
A	WO,A,93 05841 (BAXTER TRAVENOL INC,) 1 April 1993 ----	
A	WO,A,92 20397 (JANG) 26 November 1992 ----	
A	EP,A,0 441 384 (ADVANCED CARDIOVASCULAR SYSTEMS, INC) 14 August 1991 -----	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.  
PCT/US 94/07960

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-4552554	12-11-85	EP-A- 0166212	02-01-86
EP-A-0388112	19-09-90	US-A- 4932413	12-06-90
		AU-B- 610455	16-05-91
		AU-A- 5126990	13-09-90
		CA-A- 2011823	13-09-90
		DE-D- 69005334	03-02-94
		DE-T- 69005334	14-04-94
		ES-T- 2047258	16-02-94
		JP-A- 3021261	30-01-91
		US-A- 4947864	14-08-90
EP-A-0282143	14-09-88	CA-A- 1328791	26-04-94
		DE-D- 3884020	21-10-93
		DE-T- 3884020	03-03-94
		ES-T- 2043796	01-01-94
		JP-A- 63229066	22-09-88
		US-A- 4988356	29-01-91
US-A-5161534	10-11-92	NONE	
EP-A-0518205	16-12-92	US-A- 5135535	04-08-92
		JP-A- 6023055	01-02-94
WO-A-9217236	15-10-92	EP-A- 0578777	19-01-94
WO-A-9305841	01-04-93	US-A- 5324269	28-06-94
WO-A-9220397	26-11-92	AU-A- 2158092	30-12-92
		EP-A- 0586571	16-03-94
		JP-T- 6507805	08-09-94
EP-A-0441384	14-08-91	JP-A- 5084304	06-04-93